

Front Right Hand Shown

New hose to follow OEM hose routing

OEM Hardware
125 Nm / 92 lb-ft

Supplied Hardware
105 Nm / 78 lb-ft

21mm socket

10mm hex bit
(Allen Key)

Banjo bolt
20 Nm / 15 lb-ft

13mm socket

POWERBRAKE

www.powerbrake.co.za
www.powerbrakeglobal.com

Assembly diagram for bracket orientation and torque specs

DATE:	23/03/2022
VEHICLE:	Jeep Wrangler JL & Gladiator JT
KIT:	X6M / 350x34mm Stage-1
PLATFORM CODE:	JEE03F

Observe required torque specifications using an appropriate torque wrench / Do not use thread lockers on caliper mounting bolts

Brake Pad Replacement Part Numbers	
Manufacturer	Part #
FMSI	D1116
Powerbrake PB01	5001-PB01
Powerbrake PB05	5001-PB05
Endless	RCP112xx
G-Loc	GP1365
Bendix Australia	DB1845U
Mintex	MDB3115
Mintex (Alternative)	MDB3116 (lower friction)
Ferodo (Street)	FDB4212 or FDS4212
Ferodo (Race)	FRP3100
Hawk Performance	HB616x.607
Hella Pagid (Street)	8DB 355 019-521
Pagid (Race)	8005
Febi Bilstein	116138
PFC	9195

xx Designates manufacturer's friction compound. Select appropriate compound for application.
Contact our Sales Office for more info if required.

Spare Parts Numbers	
Description	Part #
Disc / Rotor Pair 350X34mm Stage-1	AT481
Caliper Seal Kit *	CSK-xx/xx/xx-O

* xx/xx/xx refers to the piston sizes of your X-Line caliper - lasered onto the inboard face of caliper body